

RedlineGoods Jeep Liberty 2008-12 Armrest Cover Installation Manual

Lift center console lid and look for the screws that hold the lid to the base.



Remove these three screws and remove the lid. Separate the top and bottom halves of the armrest. You only need the top part to install the cover.

Install the new cover onto the armrest. The new cover needs to be glued.

There are several kinds of glue that can be used, the 3M used below is just one of them.

Set up a staging area because the adhesive sprays pretty well out of the can.

Clean the console with a little soap and water to ensure that nothing interferes with the adhesive.

PRACTICE lining the leather up on the armrest. Decide where you are going to lay the leather on the console after the adhesive has been applied - once you



Redline Automotive Accessories Corp. will not be held liable for any labor, incidental or consequential damages of any kind. Proceed at your own risk.

RedlineGoods.com – All rights reserved. Use for advertising competing products will be prosecuted.

have sprayed the glue and put the parts together, it's very tough to pull apart. The leather pattern is cut precisely.

Spray the adhesive on the console and the back of the leather. Follow the directions on the can. Be careful that you don't get any on the front of the leather.

Don't worry if it looks like the adhesive seeps through to the finished side of the leather. It does leave some marks on the good side while it's wet, but that goes completely away when this dries in about an hour.

Installation is the reverse of removal.

Redline Automotive Accessories Corp. will not be held liable for any labor, incidental or consequential damages of any kind. Proceed at your own risk.